

# Baltic

## Technical Specifications

Manufacturing method	:	Level loop
Pile type	:	Looppile
Pile fibre	:	100% PA6 SD
Gauge	:	1/10"
Pile weight	:	550 gr/m <sup>2</sup>
Pile height	:	3.0 mm
Total weight	:	4.000 gr/m <sup>2</sup>
Total thickness	:	5.0 mm
Tuft density	:	177.750/m <sup>2</sup>
Tile size	:	50 x 50 cm
Backing	:	Polyflex
Tiles per box	:	20



Discover more!

## Performance

Use classification	EN 1307	:	33
Caster chair test	EN 985	:	A, Intensive use
Abrasion	EN 1963	:	Pass
Vettermann test	EN 9405	:	Pass
Dimensional stability	EN 986	:	Pass
Thermal isolation	ISO 8302	:	0.06 m <sup>2</sup> K/W
Sound absorption	ISO 140-8	:	20 dB
Luxury class	EN 1307	:	LC2
DOP-nr		:	1016-2612
Prodis-nr		:	C82D284D

## Electrostatic

Static loading		:	Anti-static
Walking test	EN 1815	:	≤ 0.3 KV
Horizontal resistance	ISO 1096 5	:	5 x 10.10 Ohm
Vertical resistance	ISO 1096 5	:	5 x 10.10 Ohm

## Flammability

Reaction to fire EN ISO 13501-1	:	Bfl-s1
Reaction to fire BS 4790	:	Low radius of effect of ignition

## Acoustics


Sound absorption EN ISO 10140	:	0.15
Impact sound insulation EN ISO 354	:	24 dB

## Colour fastness

Light	ISO 105 B02	:	7.0 - 8.0
Rubbing	ISO 105 x12	:	4.5
Water	ISO 105 E01	:	5.0

## Maintenance

Regular vacuum cleaning is essential. Spills and surface stains can be removed by sponging with a damp cloth, or for more resistant stains, with a mild detergent solution.



Betap has the right to alter each product specification in order to improve the carpet according to the newest technological applications.

