

Baltic

Technical Specifications

| | | |
|----------------------|---|-------------------------|
| Manufacturing method | : | Level loop |
| Pile type | : | Looppile |
| Pile fibre | : | 100% PA6 SD |
| Gauge | : | 1/10" |
| Pile weight | : | 550 gr/m ² |
| Pile height | : | 3.0 mm |
| Total weight | : | 1.510 gr/m ² |
| Total thickness | : | 4.5 mm |
| Tuft density | : | 177.750/m ² |
| Tile size | : | 400 cm |
| Backing | : | Actionback |



Discover more!

Performance

| | | | |
|-----------------------|-----------|---|-------------------------|
| Use classification | EN 1307 | : | 33 |
| Caster chair test | EN 985 | : | A, Intensive use |
| Abrasion | EN 1963 | : | Pass |
| Vettermann test | EN 9405 | : | Pass |
| Dimensional stability | EN 986 | : | Pass |
| Thermal isolation | ISO 8302 | : | 0.06 m ² K/W |
| Sound absorption | ISO 140-8 | : | 20 dB |
| Luxury class | EN 1307 | : | LC2 |
| DOP-nr | | : | 1016-2612 |
| Prodis-nr | | : | C82D284D |

Electrostatic

| | | | |
|-----------------------|------------|---|---------------|
| Static loading | | : | Anti-static |
| Walking test | EN 1815 | : | ≤ 0.3 KV |
| Horizontal resistance | ISO 1096 5 | : | 5 x 10.10 Ohm |
| Vertical resistance | ISO 1096 5 | : | 5 x 10.10 Ohm |

Flammability

| | | | |
|---------------------------------|--|---|----------------------------------|
| Reaction to fire EN ISO 13501-1 | | : | Bfl-s1 |
| Reaction to fire BS 4790 | | : | Low radius of effect of ignition |

Acoustics


| | | | |
|------------------------------------|--|---|-------|
| Sound absorption EN ISO 10140 | | : | 0.15 |
| Impact sound insulation EN ISO 354 | | : | 24 dB |

Colour fastness

| | | | |
|---------|-------------|---|-----------|
| Light | ISO 105 B02 | : | 7.0 - 8.0 |
| Rubbing | ISO 105 x12 | : | 4.5 |
| Water | ISO 105 E01 | : | 5.0 |

Maintenance

Regular vacuum cleaning is essential. Spills and surface stains can be removed by sponging with a damp cloth, or for more resistant stains, with a mild detergent solution.



Betap has the right to alter each product specification in order to improve the carpet according to the newest technological applications.

