

Larix

Technical Specifications

Manufacturing method	: Level loop
Pile type	: Bouclé
Pile fibre	: 100% PA6 SD
Gauge	: 5/32"
Pile weight	: 600 gr/m ²
Pile height	: 3.5 mm
Total weight	: 4200 gr/m ²
Total thickness	: 7.2 mm
Tuft density	: 177.000/m ²
Tile size	: 50 x 50 cm
Backing	: Polyflex
Tiles per box	: 20



Discover more!

Performance

Use classification	EN 1307	: 33
Caster chair test	EN 985	: A, Intensive use
Abrasion	EN 1963	: Pass
Vettermann test	EN 9405	: Pass
Dimensional stability	EN 986	: Pass
Thermal isolation	ISO 8302	: 0.09 m ² K/W
Luxury class	EN 1307	: LC2
DOP-nr		: 1016-1013

Electrostatic

Static loading		: Anti-static
----------------	--	---------------

Flammability


Reaction to fire EN ISO 13501-1		: Bfl-s1
---------------------------------	--	----------

Acoustics

Sound absorption EN ISO 10140	: 0.15
Impact sound insulation EN ISO 354	: 24 dB

Colour fastness

Light	ISO 105 B02	: 7.0 - 8.0
Rubbing	ISO 105 x12	: 4.5



Maintenance

Regular vacuum cleaning is essential. Spills and surface stains can be removed by sponging with a damp cloth, or for more resistant stains, with a mild detergent solution.



Betap has the right to alter each product specification in order to improve the carpet according to the newest technological applications.

