



Vienna Tile

Technical Specifications

Manufacturing method	: Level loop
Pile type	: Loop pile
Pile fibre	: 100% polypropylene solution-dyed
Gauge	: 1/10"
Pile weight	: 400 gr/m ²
Pile height	: 2.9 mm
Total weight	: 3700 gr/m ²
Total thickness	: 5.9 mm
Tuft density	: 193.550/m ²
Tile size	: 50 x 50 cm
Backing	: Polyflex
Tiles per box	: 20



Odkryj więcej!

made with
select yarns®

Performance

Use classification		: 31
Caster chair test	EN 985	: B, occasional use
Abrasion	EN 1963	: Pass
Vettermann test	EN 1471	: Pass
Dimensional stability	EN 986	: Pass
Thermal isolation	ISO 8302	: 0.10 m ² K/W
Luxury class		: LC1
DOP-nr		: 1016-3012

Electrostatic


Static loading		: Anti-static
----------------	--	---------------

Flammability

Reaction to fire EN ISO 9239-1		: Cfl-s1
Reaction to fire BS 4790		: Low radius of effect of ignition

Colour fastness

Light	ISO 105 B02	: 7.0 – 8.0
Rubbing	ISO 105 x12	: 4.5



Maintenance

Regular vacuum cleaning is essential. Spills and surface stains can be removed by sponging with a damp cloth, or for more resistant stains, with a mild detergent solution.



Betap has the right to alter each product specification in order to improve the carpet according to the newest technological applications.

